SUNFIRE

120,000 BTUs

HEATS UP TO 2,800 SQ. FT.







CLEAN



ODORLESS









THERMOSTAT CONTROL OPTION CONNECT TO STANDARD WALL THERMOSTAT (THERMOSTAT NOT INCLUDED)



"NO SMELL. NO FUMES."

The advanced technology burner produces a pure, clean flame for a safe indoor heating experience. The RAPID ACCESS hatch offers fast access to the nozzle assembly, making tune-ups and maintenance ultra-fast and easy.



(Hook/Strap/Forklift)

Tip Switch Inside for Safety

Thermostat
Control Option
(Thermostat not included)

Collapsable Handle

Heavy-Duty
Construction



Comfort Grip Steel Tube Frame

Quick Change Spin-On Fuel Filter

Rubber Flat Free Wheels

Easy-Fill Fuel Neck





SPECIFICATIONS				
вти/Hr:	120,000	Weight:	125 lbs. Fully Fueled: 220 lbs.	Thermostat Options:
Fuel:	Diesel, #2 Fuel Oil, Kerosene	Product Dimensions:	33"L x 28.5"W x 33.75"H	Use any mechanical or battery operated
Flow Rate GPH:	.85 Diesel and .78 Kerosene	Run Time:	16 Hrs. Diesel / 18 Hrs. Kerosene	wall thermostat. Do not use a thermostat that requires 120V of power.
Tank Capacity:	14.2 Gallons	Minimum Clearances: Keep away from combustible items.	The state of the s	
Electrical Requirements:	120V 1.2A 60HZ (800W+ Pure Sine INV)			Thermostat not included.

^{*} Requires proper ventilation. Not for indoor household residential use.

Available Accessory: Fuel-Filter Heating Band.

SUNFIRE





