SUNFIRE

150,000 BTUs

HEATS UP TO 3,500 SQ. FT.













THERMOSTAT CONTROL OPTION
CONNECT TO STANDARD WALL THERMOSTAT
(THERMOSTAT NOT INCLUDED)

RUNS ON DIESEL OR #2 FUEL OIL
REQUIRES 120V OF ELECTRICITY.

DIESEL-FUELED HEAVY DUTY HEATER



"NO SMELL. NO FUMES."

OUTPERFORMS FORCED AIR HEATERS

FORCED AIR

THE PROBLEM

- × EXTREMELY LOUD
- × STRONG ODOR
- × SHORTER RUN TIMES
- × HEATS AIR, NOT OBJECTS

SUNFIRE RADIANT

THE SOLUTION

- **✓ LOW NOISE**
- VIRTUALLY ODORLESS
- LONG RUN TIMES
- **✓ HEATS OBJECTS DIRECTLY**



Requires proper ventilation, not for industriola residential use.					
SPECIFICATIONS					
вт∪/Hr:	High: 150,000 (43kW) Low: 130,000 (38kW)	Weight:	Empty Tank: 195 lbs. Full Tank: 320 lbs.	Thermostat Options:	
Fuel:	Types: Diesel, #2 Fuel Oil Tank Capacity: 19 Gallons	Product Dimensions:	35"W x 29"L x 41"H 88.9cm x 73.7cm x 104.1cm	Use any mechanical or battery operated wall thermostat. Do not use a thermostat	
Flow Rate:	High: 1.10 GPH Low: .97 GPH	Run Time:	High: 17 Hrs Low: 19 Hrs	that requires 120V of electricity to operate.	
Electrical Requirements:	120V 2A 60HZ Or 12V Pure Sine Inverter (800W Min)	Minimum Clearances: Keep away from combustible items.	Front: 72" Sides: 36" Back: N/A	Thermostat not included. See manual for quick installation.	







